

The Super Twister 12 volt pump is capable of pumping up to 85 feet from at an amazing 1.0 gallon per minute from ground level by simply connecting the pump to a 12 volt battery. This Revolutionary 3 stage pump has a constant voltage booster (CVB) built into the pump. The (CVB) outputs a constant voltage to the Super Twister Pump motors which reduces voltage drop due to battery drainage. What does that mean? A more continuous and faster discharge rate! The Super Twister reliable design is suitable for continuous sampling or purging of groundwater wells. The Super Twister is not designed for use with the Low Flow Sampling Controller.

***Simplify and Expedite Your Next Sampling Event!***

The Super Twister can pass sand, small rocks and debris without getting clogged or damaging the pump motors!

The Super Twister can run continuously without the need for a cool down!  
It can also run dry for up to two hours without motor damage!



The Super Twister can also run dry for up to two hours without motor damage!

The Super Twister has a long lasting 400 hour motor life!

The Super Twister's (CVB) incorporates a Reverse Polarity Protection fuse. It has sleek outside that minimizes well hang-ups.

The Super Twister is a very reliable and economical pump that provides a great bang for your buck!

The Super Twister comes ready for field use; with 90 feet of heavy duty wire and alligator battery clamps and it is shipped in its own box.

**SPECS:**

POWER CONSUMPTION:	150-195 WATTS (MAX)
VOLT RECOMMENDATION:	12 - 15 At Source
MAXIMUM AMP OUTPUT:	18 AMPS
MEASUREMENTS:	LENGTH 15" / DIAMETER: 1.7"
CONSTRUCTED:	PVC PLASTIC & STAINLESS STEEL
DISCHARGE OUTLET:	3/8" ID OR 1/2" ID POLY TUBING CAN BE USED
SUPPLIED WITH:	90 FEET OF HEAVY DUTY 12 GAUGE WIRE / BATTERY CLAMPS

**Super Twister Pump Chart**

PUMPING DEPTH (DTW)	GALLONS PER MINUTE
3	3.75
10	2.5
20	2.00
25	1.75
30	1.65
40	1.50
50	1.25
55	1.0
60	0.85
70	0.75
85	0.50
90	N/A

